

Nominal Diameter	25 cm / 10 "
Rated Impedance	8
Reference efficiency (1W @ 1m)	99 dB SPL
Power Handling Capacity	250 W AES
SPL max (continuous)	119 dB SPL
Usable frequency range	120 - 3000 Hz
Speaker net mass	8.2 kg

Architecture highlights :

- Very high sensitivity & SPLmax 10" Midrange driver with low THD level
- Midrange unit with critical damping diaphragm
- High definition CCAR vented voice-coil
- Natural convection Intercooler System



Motor architecture			
Voice coil diameter	mm		77
Voice coil length	mm		12
Air gap height	mm		10

Typical characteristics			
Rated impedance	Z	Ω	8
Half space sensitivity (1W@1m)	-	dB SPL	99
Usable freq. range	-	Hz	120 - 3000
Power handling capacity (AES)	-	W	250
Max Sound Pressure Level	SPL _{max}	dB SPL	119
Min. impedance modulus	Z _{min}	Ω @Hz	6.7@550
Voice-coil inductance @ 1kHz	Le _{1k}	mH	1.154
Voice-coil inductance @ 10kHz	Le _{10k}	mH	0.550
BL product	BL	N/A	21.1
Moving mass	Mms	kg	0.038

Thiele-Small parameters			
Resonance frequency	Fs	Hz	90 (± 18)
DC Resistance	Re	Ω	5.5 (± 0.6)
Mechanical quality factor	Qms		2.98
Electrical quality factor	Qes		0.27
Total quality factor	Qts		0.24
Suspension compliance	Cms	10^{-6} .m/N	80
Effective piston area	Sd	m ²	0.0377
Equivalent Cas air load	Vas	m ³	0.0163
Max linear excursion	Xmax	mm	± 2.0
Linear displacement volume	Vd	10^{-3} .m ³	0.0753
Reference efficiency	η_0	%	4.3
Unity load volume	Vas.Qts ²	10^{-3} .m ³	1.0

Absolute maximum ratings			
Short term max. input voltage	Vmax	V	90
Max.excursion before damage	Xdam	mm	4.0
Ambient operating temperature	Ta	$^{\circ}$ C	-10 to +50
Storage temperature		$^{\circ}$ C	-20 to +70
Environmental withstanding			humidityproof

Mounting information			
Air volume occupied by the driver	10^{-3} .m ³		2.0
Speaker net mass	kg		8.2
Baffle cut-out diameter (front mounting)	mm		229.0
Bolt number & Metric diameter	-		6x M5
Bolt circle diameter	mm		266.0
Max overall dimension (on ears)	mm		283.5
Max overall dimension (out of ears)	mm		255.0
Flange height	mm		11.0
Max magnet diameter	mm		204.0
Max depth (front mounting)	mm		113.0
Recommended reflex box	Lts / Hz		4 - 6L sealed
Electrical connection			$\varnothing 4$ mm Push buttons

