

Nominal Diameter	<b>38 cm / 15 "</b>
Rated Impedance	<b>8</b>
Reference efficiency (1W @ 1m)	<b>97 dB SPL</b>
Power Handling Capacity	<b>500 W AES</b>
SPL max (continuous)	<b>120 dB SPL</b>
Usable frequency range	<b>40 - 2000 Hz</b>
Speaker net mass	<b>7.7 kg</b>

### Architecture highlights :

- Natural convection Intercooling System
- Both sides coated Curvilinear cone (Tropical withstanding)
- High compliance double half-roll fabric surround
- Ultra light injection molded basket



Motor architecture			
Voice coil diameter	mm		77
Voice coil length	mm		20
Air gap height	mm		10

Typical characteristics			
Rated impedance	Z	$\Omega$	8
Half space sensitivity (1W@1m)	-	dB SPL	97
Usable freq. range	-	Hz	40 - 2000
Power handling capacity (AES)	-	W	500
Max Sound Pressure Level	SPL <sub>max</sub>	dB SPL	120
Min. impedance modulus	Z <sub>min</sub>	$\Omega$ @Hz	4.6@250
Voice-coil inductance @ 1kHz	Le <sub>1k</sub>	mH	1.671
Voice-coil inductance @ 10kHz	Le <sub>10k</sub>	mH	0.695
BL product	BL	N/A	23.4
Moving mass	Mms	kg	0.115

Thiele-Small parameters			
Resonance frequency	Fs	Hz	40 ( $\pm 5$ )
DC Resistance	Re	$\Omega$	5.6 ( $\pm 0.6$ )
Mechanical quality factor	Qms		3.61
Electrical quality factor	Qes		0.30
Total quality factor	Qts		0.27
Suspension compliance	Cms	$10^{-6}$ .m/N	140
Effective piston area	Sd	m <sup>2</sup>	0.0892
Equivalent Cas air load	Vas	m <sup>3</sup>	0.1533
Max linear excursion	Xmax	mm	$\pm 7.5$
Linear displacement volume	Vd	$10^{-3}$ .m <sup>3</sup>	0.6690
Reference efficiency	$\eta_0$	%	3.2
Unity load volume	Vas.Qts <sup>2</sup>	$10^{-3}$ .m <sup>3</sup>	11.4

Absolute maximum ratings			
Short term max. input voltage	Vmax	V	125
Max.excursion before damage	Xdam	mm	14.0
Ambient operating temperature	Ta	$^{\circ}$ C	-10 to +50
Storage temperature		$^{\circ}$ C	-20 to +70
Environmental withstanding			tropical

Mounting information			
Air volume occupied by the driver	$10^{-3}$ .m <sup>3</sup>		4.4
Speaker net mass	kg		7.7
Baffle cut-out diameter (front mounting)	mm		356.0
Bolt number & Metric diameter	-		8x M6
Bolt circle diameter	mm		370 & 388
Max overall dimension (on ears)	mm		406.5
Max overall dimension (out of ears)	mm		380.5
Flange height	mm		13.0
Max magnet diameter	mm		204.0
Max depth (front mounting)	mm		155.5
Recommended reflex box	Lts / Hz		65L / 46Hz
Electrical connection			$\varnothing$ 4 mm Push buttons

