

Nominal Diameter	46 cm / 18 "
Rated Impedance	8
Reference efficiency (1W @ 1m)	97.5 dB SPL
Power Handling Capacity	1200 W AES
SPL max (continuous)	125 dB SPL
Usable frequency range	25 - 800 Hz
Speaker net mass	7.4 kg

Architecture highlights :

- Forced-air Intercooling System for low thermal compression
- Neodymium magnet system with symmetric BL(x) and Le(x) characteristics
- Both sides coated curvilinear cone (Tropical withstanding)
- Heavy duty long excursion suspension with linear behavior for large signal



Motor architecture			
Voice coil diameter	mm		101
Voice coil length	mm		25
Air gap height	mm		10

Typical characteristics			
Rated impedance	Z	Ω	8
Half space sensitivity (1W@1m)	-	dB SPL	97.5
Usable freq. range	-	Hz	25 - 800
Power handling capacity (AES)	-	W	1200
Max Sound Pressure Level	SPL _{max}	dB SPL	125
Min. impedance modulus	Z _{min}	Ω @Hz	6.6@190
Voice-coil inductance @ 1kHz	Le _{1k}	mH	1.914
Voice-coil inductance @ 10kHz	Le _{10k}	mH	0.839
BL product	BL	N/A	28.0
Moving mass	Mms	kg	0.217

Thiele-Small parameters			
Resonance frequency	Fs	Hz	34 (± 5)
DC Resistance	Re	Ω	5.2 (± 0.5)
Mechanical quality factor	Qms		3.86
Electrical quality factor	Qes		0.31
Total quality factor	Qts		0.28
Suspension compliance	Cms	10^{-6} .m/N	100
Effective piston area	Sd	m ²	0.1250
Equivalent Cas air load	Vas	m ³	0.2210
Max linear excursion	Xmax	mm	± 10.0
Linear displacement volume	Vd	10^{-3} .m ³	1.2504
Reference efficiency	η_0	%	2.7
Unity load volume	Vas.Qts ²	10^{-3} .m ³	17.9

Absolute maximum ratings			
Short term max. input voltage	Vmax	V	195
Max.excursion before damage	Xdam	mm	21.0
Ambient operating temperature	Ta	$^{\circ}$ C	-10 to +50
Storage temperature		$^{\circ}$ C	-20 to +70
Environmental withstanding			Tropical

Mounting information			
Air volume occupied by the driver	10^{-3} .m ³		6.2
Speaker net mass	kg		7.4
Baffle cut-out diameter (front mounting)	mm		422.0
Bolt number & Metric diameter	-		8x M6
Bolt circle diameter	mm		454.0
Max overall dimension (on ears)	mm		476.0
Max overall dimension (out of ears)	mm		457.0
Flange height	mm		15.0
Max magnet diameter	mm		140.0
Max depth (front mounting)	mm		185.0
Recommended reflex box	Lts / Hz		180L / 35Hz
Electrical connection			\varnothing 4 mm Push buttons

