

Nominal Diameter	13 cm / 5 "
Rated Impedance	8
Reference efficiency (1W @ 1m)	92 dB SPL
Power Handling Capacity	100 W AES
SPL max (continuous)	109 dB SPL
Usable frequency range	110 - 4000 Hz
Speaker net mass	0.98 kg

Architecture highlights :

- Noiseless natural convection Intercooling System
- Neodymium magnet system with symmetric BL(x) and Le(x)
- High excursion fabric surround
- Lightweight basket



Motor architecture			
Voice coil diameter	mm		38
Voice coil length	mm		12
Air gap height	mm		6

Typical characteristics			
Rated impedance	Z	Ω	8
Half space sensitivity (1W@1m)	-	dB SPL	92
Usable freq. range	-	Hz	110 - 4000
Power handling capacity (AES)	-	W	100
Max Sound Pressure Level	SPL _{max}	dB SPL	109
Min. impedance modulus	Z _{min}	Ω @Hz	6.4@650
Voice-coil inductance @ 1kHz	Le _{1k}	mH	0.590
Voice-coil inductance @ 10kHz	Le _{10k}	mH	0.233
BL product	BL	N/A	8.8
Moving mass	Mms	kg	0.009

Thiele-Small parameters			
Resonance frequency	Fs	Hz	130 (± 20)
DC Resistance	Re	Ω	5.7 (± 0.6)
Mechanical quality factor	Qms		3.96
Electrical quality factor	Qes		0.55
Total quality factor	Qts		0.49
Suspension compliance	Cms	10^{-6} .m/N	160
Effective piston area	Sd	m ²	0.0106
Equivalent Cas air load	Vas	m ³	0.0025
Max linear excursion	Xmax	mm	± 4.5
Linear displacement volume	Vd	10^{-3} .m ³	0.0476
Reference efficiency	η_0	%	1.0
Unity load volume	Vas.Qts ²	10^{-3} .m ³	0.6

Absolute maximum ratings			
Short term max. input voltage	Vmax	V	55
Max. excursion before damage	Xdam	mm	± 9
Ambient operating temperature	Ta	$^{\circ}$ C	-10 to +50
Storage temperature		$^{\circ}$ C	-20 to +70
Environmental withstanding			Outdoor+

Mounting information		
Air volume occupied by the driver	10^{-3} .m ³	0.18
Speaker net mass	kg	0.98
Baffle cut-out diameter (front mounting)	mm	124.50
Bolt number & Metric diameter	-	4x M5
Bolt circle diameter	mm	147.00
Max overall dimension (on ears)	mm	163.0
Max overall dimension (out of ears)	mm	136.0
Flange height	mm	12.50
Max magnet diameter	mm	-
Max depth (front mounting)	mm	76.00
Recommended reflex box	Lts / Hz	5L / 110Hz
Electrical connection	6.35x0.8 + 4.8x0.5 FASTON	

