

Nominal Diameter	30 cm / 12 "
Rated Impedance	8
Reference efficiency (1W @ 1m)	97 dB SPL
Power Handling Capacity	400 W AES
SPL max (continuous)	120 dB SPL
Usable frequency range	50 - 2500 Hz
Speaker net mass	6.3 kg

Architecture highlights :

- Noiseless Natural Convection Intercooling System
- Front side coated curvilinear cone designed for 2 way systems operation
- Neodymium magnet System with symmetric BL(x) and Le(x) characteristics
- Coaxial apparatus "-19" with 2x M6 on Ø 76.2 mm
(Max diameter for HF driver = 144.0 mm)



Motor architecture			
Voice coil diameter	mm		77
Voice coil length	mm		17
Air gap height	mm		8

Typical characteristics			
Rated impedance	Z	Ω	8
Half space sensitivity (1W@1m)	-	dB SPL	97
Usable freq. range	-	Hz	50 - 2500
Power handling capacity (AES)	-	W	400
Max Sound Pressure Level	SPL _{max}	dB SPL	120
Min. impedance modulus	Z _{min}	Ω@Hz	6.1@310
Voice-coil inductance @ 1kHz	Le _{1k}	mH	1.295
Voice-coil inductance @ 10kHz	Le _{10k}	mH	0.584
BL product	BL	N/A	23.0
Moving mass	Mms	kg	0.069

Thiele-Small parameters			
Resonance frequency	Fs	Hz	46 (±5)
DC Resistance	Re	Ω	4.9 (±0.5)
Mechanical quality factor	Qms		4.99
Electrical quality factor	Qes		0.18
Total quality factor	Qts		0.18
Suspension compliance	Cms	10 ⁻⁶ .m/N	170
Effective piston area	Sd	m ²	0.0493
Equivalent Cas air load	Vas	m ³	0.0590
Max linear excursion	Xmax	mm	± 6.0
Linear displacement volume	Vd	10 ⁻³ .m ³	0.2957
Reference efficiency	η ₀	%	3.0
Unity load volume	Vas.Qts ²	10 ⁻³ .m ³	1.9

Absolute maximum ratings			
Short term max. input voltage	Vmax	V	115
Max.excursion before damage	Xdam	mm	16.0
Ambient operating temperature	Ta	°C	-10 to +50
Storage temperature		°C	-20 to +70
Environmental withstanding			humidityproof

Mounting information			
Air volume occupied by the driver	10 ⁻³ .m ³		2.10
Speaker net mass	kg		6.30
Baffle cut-out diameter (front mounting)	mm		282.0
Bolt number & Metric diameter	-		8x M6
Bolt circle diameter	mm		300 to 308
Max overall dimension (on ears)	mm		326.5
Max overall dimension (out of ears)	mm		307.0
Flange height	mm		13.0
Max magnet diameter	mm		140.0
Max depth (front mounting)	mm		141.5
Recommended reflex box	Lts / Hz		35L / 63Hz
Electrical connection			Ø4 mm Push buttons

