



PHL Audio HP951Nd

5 inches midrange driver

Nominal Diameter	13 cm / 5 "
Rated Impedance	16 Ω
Reference efficiency (1W @ 1m)	94 dB SPL
Power Handling Capacity	80 W AES
SPL max (continuous)	110 dB SPL
Usable frequency range	110 - 4000 Hz
Speaker net mass	0.98 kg

Architecture highlights :

- Noiseless natural convection Intercooling System
- Neodymium magnet system with symmetric BL(x) and Le(x)
- High definition CCAR vented voice coil
- Critical damping flat foam surround
- Lightweight basket

Motor architecture

Voice coil diameter	mm	38
Voice coil length	mm	7.5
Air gap height	mm	6

Typical characteristics

Rated impedance	Z	Ω	16
Half space sensitivity (1W@1m)	-	dB SPL	94
Usable freq. range	-	Hz	110 - 4000
Power handling capacity (AES)	-	W	80
Max Sound Pressure Level	SPL _{max}	dB SPL	110
Min. impedance modulus	Z _{min}	Ω @Hz	12.9@600
Voice-coil inductance @ 1kHz	Le _{1k}	mH	1.099
Voice-coil inductance @ 10kHz	Le _{10k}	mH	0.505
BL product	BL	N/A	13.2
Moving mass	Mms	kg	0.008

Thiele-Small parameters

Resonance frequency	Fs	Hz	200 (± 40)
DC Resistance	Re	Ω	11.6 (± 1.2)
Mechanical quality factor	Qms	1	5.15
Electrical quality factor	Qes	1	0.69
Total quality factor	Qts	1	0.61
Suspension compliance	Cms	10 ⁻⁶ .m/N	80
Effective piston area	Sd	m ²	0.0109
Equivalent Cas air load	Vas	m ³	0.0013
Max linear excursion	Xmax	mm	± 2.5
Linear displacement volume	Vd	10 ⁻³ .m ³	0.0273
Reference efficiency	η_0	%	1.5
Unity load volume	Vas.Qts ²	10 ⁻³ .m ³	0.5

Absolute maximum ratings

Short term max. input voltage	Vmax	V	70
Max.excursion before damage	Xdam	mm	± 3
Ambient operating temperature	Ta	°C	-10 to +50
Storage temperature		°C	-20 to +70
Environmental withstanding			humidity proof



Mounting information

Air volume occupied by the driver	10 ⁻³ .m ³	0.18
Speaker net mass	kg	0.98
Baffle cut-out diameter (front mounting)	mm	124.5
Bolt number & Metric diameter	-	4x M5
Bolt circle diameter	mm	147.0
Max overall dimension (on ears)	mm	163.0
Max overall dimension (out of ears)	mm	136.0
Flange height	mm	12.5
Max magnet diameter	mm	-
Max depth (front mounting)	mm	76.0
Recommended reflex box	Lts / Hz	1.5L sealed
Electrical connection	6.35x0.8 + 4.8x0.5 FASTON	

